*Part Number: 5602, 5616, 5617*

# **5600 Series** Thin Clients

## *Performance Class*

The 5600 Series Thin Clients are designed for knowledge based tasks and content creation. These units combines the power and technology of the industry-leading Intel Atom N270 1.6GHz processor and the smallest form factor unit on the market, making the 5600 Series a well-rounded, high performance and versatile unit for any desktop platform.

Known for its exceptional graphics performance, the 5600 Series allows the user to experience the capabilities of video streaming, rich multi-media content and multiple appliances. The 5600 range also offers the versatility of adding an additional monitor to expand the functionality and performance of the end users experience. These Thin Clients offer impressive features and benefits without compromising the users precious desktop workspace. They also come with a removable stand and an optional VESA mounting bracket allowing the unit to be mounted on the back of the monitor, on a wall or in a cabinet if required, to maximize on space-saving.

The Linux Thin Client supports three modes of operation; Desktop Mode, WBT Mode and Kiosk Mode.

| | |
|---|---|
| ▶ Small Form Factor | ▶ 802.11 b/g/n Wireless Capable |
| ▶ Powerful Intel Atom 1.6GHz Processor | ▶ VESA Mounting Capabilities |
| ▶ Dual Monitor Option | ▶ Centralized Manangement |

P: 866-865-5250 I E: info@10ZiG.com I W: www.10ZiG.com

# 5600 Series Thin Clients

## 5600 Series Models

| | |
|---|---|
| **System** | |
| Management | 10ZiG Centralized Manangement Utility |
| Form Factor | Ultra Mini |
| Processor | Intel Atom N270 1.6GHz |
| Chipset | Intel 945GSE Integrated Graphics Media Accelerator 950 |
| **Dimensions** | |
| Device | 1.4"(W) x 6.1"(H) x 4.8"(D) |
| Weight | 1.5 lbs |
| **Connections** | |
| Ports | USB x 4, PS2 x 1, Line-Out x 1, Mic-In x 1, Internal Speaker x 1 |
| Video | DVI-I x 1, 1920 x 1200 x 32 (24 on Linux) Bit Color |
| **Networking** | |
| Wireless | Optional Internal Wireless 802.11 b/g/n |
| Ethernet | 10/100/1000 Base-T, PXE |
| **Environmental** | |
| Operating Temp. | 32~95F (0~35C), 20-80% non-condensing humidity |
| Power | 12 Watt Consumption, 36 Watt, DC-12V/3A Input |

***WARRANTY: All Thin Clients include a 3-Year Advanced Warranty***

**SPECIFICATIONS:**

1. Power Button (LED inside)
2. Network Light
3. Audio Out
4. Mic In
5. Front USB (x2)
6. Stand
7. Ethernet 10/100/1000
8. Back USB (x2)
9. DVI Socket
10. PS2 Keyboard Port
11. Power
12. Kensington Lock

| | 5602 | 5616 | 5617 |
|---|---|---|---|
| **Operating System** | 10ZiG Linux | WES 2009 | WES7 |
| **Memory** | | | |
| RAM | STD: 1GB<br>MAX: 2GB | STD: 1GB<br>MAX: 2GB | STD: 2GB<br>MAX: 2GB |
| Storage | STD: 1GB<br>MAX: 2GB | STD: 2GB<br>MAX: 16GB | STD: 4GB<br>MAX: 16GB |
| **Software** | | | |
| Software Applications | Firefox, Citrix Receiver, RDP, TN5250e/TN3270e Sessions, PuTTY with optional Ericom PowerTerm, Sun JVM, VNC, Adobe Flash, Email | Internet Explorer, Citrix Receiver, RDP, Sun JVM, VNC, Adobe Flash, TN5250e/TN3270e Sessions, SSL and SSO | Internet Explorer, Citrix Receiver,RDP, Sun JVM, VNC, Adobe Flash, TN5250e/TN3270e Sessions, SSL and SSO |
| VDI Connection Brokers | Citrix XenDesktop with HDX, VMware View with PCoIP, VDI-In-a-Box, RedHat, 2X, Quest vWorkspace, Ericom, Leostream | Citrix XenDesktop with HDX, VMware View with PCoIP, VDI-In-a-Box * | Citrix XenDesktop with HDX, VMware View with PCoIP, VDI-In-a-Box * |

**** Optional VDI Brokers Available: Quest vWorkspace, Ericom, Leostream, RedHat, 2X***


**linkedin.com/company/10ZiG-Technology**

**www.facebook.com/10ZiGTechnology**

**@10zigtechnology**

**10ZiG.com/smpk**

**sales@10ZiG.com • (866) 865-5250**

**www.10ZiG.com**